RECEIVED
CENTRAL FAX CENTER

MAR 0 4 2005

App. No. 10/085,552 Amendment dated March 3, 2005 Reply to Office action of December 3, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the present application.

Listing of Claims:

Claim 1 (currently amended): A method for non-invasively profiling, using the C/V technique, carrier concentration in a wafer including [[an]] a plurality of in-containing-compound semiconductor surface layer layers, wherein the carrier concentration profiling method includes:

contacting a liquid electrode superficially on the wafer; and employing [[an]] applied voltage being up to voltages, including at least a maximum voltage surpassing that surpasses 10V, to profile the wafer's C/V characteristics without using photo-etching.

Claim 2 (original): The carrier concentration profiling method set forth in claim 1, wherein an aqueous EDTA solution is utilized as the liquid electrode.

Claim 3 (original): The carrier concentration profiling method set forth in claim 2, wherein the aqueous EDTA solution contains 80% or more EDTA.

Claim 4 (original): The carrier concentration profiling method set forth in claim 1, wherein liquid tiron is utilized as the liquid electrode.

Claim 5 (original): The carrier concentration profiling method set forth in claim 1, wherein a metal Ga melt is utilized as the liquid electrode.

Claim 6 (currently amended): A method for profiling, using the C/V technique, carrier concentration in a wafer including [[an]] a plurality of In-

App. No. 10/085,552 Amendment dated March 3, 2005 Reply to Office action of December 3, 2004

containing-compound semiconductor surface layer <u>layers</u>, wherein the carrier concentration profiling method includes:

superficially contacting the wafer with and thereafter solidifying a metal Ga melt, to form a metal Ga electrode;

employing [[an]] applied voltage being up to <u>voltages, including at least</u> a <u>maximum</u> voltage surpassing that surpasses 10V, to profile the wafer's carrier concentration; and

subsequent to the profiling, melt-clearing the metal Ga electrode.

Claim 7 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 8 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 1, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 9 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 2, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 10 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 3,

App. No. 10/085,552 Amendment dated March 3, 2005 Reply to Office action of December 3, 2004

whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 11 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 4, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 12 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 5, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 13 (withdrawn): A compound semiconductor wafer including an Incontaining-compound semiconductor surface layer, wherein carrier concentration in the wafer is non-invasively profiled according to the method set forth in claim 6, whereby its carrier concentration having been non-invasively profiled the wafer can be employed as it is for device processing.

Claim 14 (new): A method utilizing a *C/V* analyzer including a light-receiving-windowless cell to profile non-invasively, without using photoetching, carrier concentration in a semiconductor substrate composed of an in-containing compound and superficially onto which at least one incontaining-compound semiconductor layer has been heteroepitaxially grown, the method consisting essentially of the steps of:

filling the cell with one liquid selected from an aqueous EDTA solution containing 80% or more EDTA, liquid tiron, and a metal Ga melt;

ジャッジパテントファーム Mar 4 2005 14:08 P.04/06

App. No. 10/065,552 Amendment dated March 3, 2005 Reply to Office action of December 3, 2004

placing the wafer on an opening in the cell so as to put the liquid in superficial contact with the wafer to allow the liquid to function as an electrode; and

employing applied voltages, including at least a maximum voltage that surpasses 10V, to profile the wafer's C/V characteristics.